

XI'AN FUNCTION MATERIAL GROUP CO., LTD Material Safety Data Sheet Magnesium Oxide-doped Zinc Oxide

1. Product and Company Identification		
Trade Name:	Magnesium Oxide-doped Zinc Oxide	
Chemical Formula:	ZnO-MgO	
Manufaaturar/Cumplian	VI AN EUNCTION MATERIAL CROUP CO. 1 TO	
Manufacturer/Supplier: Street:	XI'AN FUNCTION MATERIAL GROUP CO., LTD No. 69, Gazelle Valley, High-Tech Zone	
City:	XI'AN	
State:	Shaanxi	
Zip Code:	710077	
Country:	China	
Tel #:	+86-29-88993870/+86-13519132051	
	2. Hazards Identification	
Signal Word:	Warning	
Hazard Statements:	H410: Very toxic to aquatic life with long lasting effects	
Precautionary Statements:	P273: Avoid release to the environment P391: Collect spillage P501: Dispose of contents/container in accordance with local/regional/national/international regulations	
HMIS Health Ratings (0-4):		
Health:	1	
Flammability:	0	
Physical:	0	
	3. Composition	
Chemical Family:	Nonmetal	
Additional Names:	None	
Zinc oxide (ZnO):		
Percentage:	0-100 wt%	
CAS #:	1314-13-2	
EC #:	215-222-5	
Magnesium oxide (MgO):		
Magnesium oxide (MgO): Percentage:	0-100 wt%	
	0-100 wt% 1309-48-4	

	4. First Aid Procedures
General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult. Keep patient warm. Seek immediate medical attention.
Ingestion:	Seek immediate medical attention.
Skin:	Immediately wash affected area with mild soap and water. Remove any
SKIII.	contaminated clothing. Seek immediate medical attention.
Eyes:	Flush eyes with water, blinking often for several minutes. Remove
	contact lenses if present and easy to do. Continue rinsing. Seek
	immediate medical attention.
	5. Firefighting Measures
– Flammability:	Non-flammable, except as powder
Extinguishing Media:	No special restrictions – use suitable extinguishing agent for
	surrounding material and type of fire.
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective
	clothing to prevent contact with skin and eyes. See section 10 for
	decomposition products.
	6. Accidental Release Measures
If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in
	special protection information. Keep unprotected persons away. Isolate
	spill area and provide ventilation. Vacuum up spill using a high
	efficiency particulate absolute (HEPA) air filter and place in a closed
Environmental Precautions:	container for disposal. Take care not to raise dust. Isolate runoff to prevent environmental pollution.
Environmental Precautions.	isolate runom to prevent environmental ponution.
	7. Handling and Storage
Handling Conditions:	Avoid contact with skin and eyes. Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store away from oxidizing agents, acids. Material is air and moisture sensitive. Store
	apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before
	eating and smoking. Do not blow dust off clothing or skin with
X7 /1 /1	compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.
	Exposure Controls and Personal Protection
8. E	Aposule controls and refsonal rotection
8. E Permissible Exposure Limits: Threshold Limit Value:	15 mg/m ³ as MgO, long-term value 10 mg/m ³ as MgO, long-term value
Permissible Exposure Limits:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous
Permissible Exposure Limits: Threshold Limit Value:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per
Permissible Exposure Limits: Threshold Limit Value: Special Equipment:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.
Permissible Exposure Limits: Threshold Limit Value: Special Equipment: Respiratory Protection:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Dust Respirator
Permissible Exposure Limits: Threshold Limit Value: Special Equipment: Respiratory Protection:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Dust Respirator Nitrile rubber gloves with minimum thickness of 0.11 mm
Permissible Exposure Limits: Threshold Limit Value: Special Equipment: Respiratory Protection: Protective Gloves: Eye Protection:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Dust Respirator Nitrile rubber gloves with minimum thickness of 0.11 mm Safety glasses or goggles
Permissible Exposure Limits: Threshold Limit Value: Special Equipment: Respiratory Protection: Protective Gloves:	 15 mg/m³ as MgO, long-term value 10 mg/m³ as MgO, long-term value Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Dust Respirator Nitrile rubber gloves with minimum thickness of 0.11 mm

9. Physical and Chemical Characteristics		
Color	White	
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts	
Odor:	Odorless	
Water Solubility:	N/A	
Boiling Point:	N/A	
Melting Point:	N/A	
Flash Point:	N/A	
	N/A	
Autoignition Temperature:		
Density:	N/A	
Molecular weight:	N/A	
	10. Reactivity	
Stability:	Stable under recommended storage conditions	
Reacts With:	Oxidizing agents, acids, alkali metals, alkaline earth metals,	
	phosphorous pentachloride	
Incompatible Conditions:	Water/moisture, air	
Hazardous Decomposition Products:	Metal oxide fume, magnesium oxide, zinc oxide	
	Metal Oxide Tulle, magnesium Oxide, zine Oxide	
	11. Toxicological Information	
Potential Health Effects:		
Eyes:	May cause irritation	
Skin:	May cause irritation	
Ingestion:	May cause irritation	
Inhalation:	May cause irritation	
Chronic:	Ingestion or inhalation of a large quantity may cause a feverish reaction	
emonie.	and leukocytosis, diarrhea. Zinc oxide dust or fume can irritate the	
	respiratory tract. Prolonged skin contact can produce a severe	
	dermatitis called oxide pox. Exposure to high levels of dust or fume car	
	cause metallic taste, marked thirst, coughing, fatigue, weakness,	
	muscular pain, and nausea followed by fever and chills. Severe	
	overexposure may result in bronchitis or pneumonia with a bluish tint	
	to the skin, prolonged or repeated exposure can cause reversible liver	
	enzyme abnormalities.	
	enzyme abnormanues.	
Signs & Symptoms:	N/A	
Aggravated Medical Conditions:	N/A	
Median Lethal Dose:	7,950 mg/kg for mouse by mouth as ZnO	
Carcinogan	IARC: No component of this product present at levels greater than or	
Carcinogen:		
	equal to 0.1% is identified as probable, possible or confirmed human	
	carcinogen by IARC.	
	NTP: No component of this product present at levels greater than or	
	equal to 0.1% is identified as a known or anticipated carcinogen by	
	NTP.	
	OSHA: No component of this product present at lovals greater then or	
	OSHA: No component of this product present at levels greater than or	
	equal to 0.1% is identified as a carcinogen or potential carcinogen by	
	equal to 0.1% is identified as a carcinogen or potential carcinogen by	
Aquatic Toxicity:	equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. 12. Ecological Information Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 1.1	
Aquatic Toxicity:	equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. 12. Ecological Information	
Aquatic Toxicity:	equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. 12. Ecological Information Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 1.1	

Persistent Bioaccumulation Toxicity: Very Persistent, Very Bioaccumulative: Notes:	 N/A N/A Do not allow material to be released to the environment without proper governmental permits. Do not allow undiluted product or large quantities to reach ground water, water course or sewage system. Danger to drinking if even small quantities leak into the ground. Poisonous for fish and plankton in water bodies. May cause long lasting harmful effects to aquatic life. Avoid transfer into the environment. Very toxic for aquatic organisms. 	
	13. Disposal Considerations	
Dispose of in accordance with local, state,	national, and international regulations.	
	14. Transportation Data	
Hazardous:	Hazardous as powder only.	
Hazard Class:	9 Miscellaneous hazardous material	
Packing Group:	Ш	
UN Number: Proper Shipping Name:	UN3077 Environmentally hazardous substance, solid, n.o.s. (Magnesium Oxide- doped Zinc Oxide)	
	15. Regulatory Information	
Sec 302 Extremely Hazardous:	No	
Sec 304 Reportable Quantities:	N/A	
Sec 313 Toxic Chemicals:	Yes	
	16. Other Information	
This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The informatio		

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

08/09/2018